

## ABS Plastic Humidifying Hollow Cone Spray Nozzles



FL-9 , 3/8" , 1/2" (Female )

### FL-9 Performance data

Orifice Performance Pressure (bar)	3 mm			4 mm			5 mm			6 mm		
	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)
1.0	167	89	0.90	210	92	0.92	264	93	0.98	320	95	1.10
1.5	205	91	0.94	255	94	0.96	326	95	1.10	392	98	1.28
2.0	237	94	0.98	295	96	1.10	372	97	1.20	460	100	1.45
2.5	259	96	1.05	328	98	1.30	420	100	1.35	510	102	1.62
3.0	295	98	1.15	355	102	1.40	465	102	1.45	550	104	1.83

ABS Plastic Humidifying Hollow Cone Spray Nozzles have the following features:

- ABS Plastic Humidifying Hollow Cone Spray Nozzles are of good corrosion resistance
- Work under low pressure with atomized spraying
- Max passage ensure the nozzles clog free
- Spray angles: 95° to 104°
- Connections: 3/8" , 1/2" ( Female )
- General Application :

Cooling

Dust suppression

Chemical treatment

Washing or cleaning