

## FL-4 ABS Whirljet Right Angle Hollow Cone Spray Nozzles



FL-4 1/2" (Female)

### FL-4 Performance data

Orifice Performance Pressure (bar)	4 mm			5 mm			6 mm			8 mm		
	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)	Flow (L/h)	Spray Angle	Spray Distance (m)
1.0	286	89	1.8	480	90	2	560	95	2.1	760	98	2.3
1.5	325	91	1.94	550	92	2.1	689	97	2.2	930	100	2.4
2.0	406	93	2.07	620	93	2.2	800	98	2.3	1100	102	2.5
2.5	470	94	2.26	680	95	2.28	900	99	2.45	1220	104	2.6
3.0	510	96	2.32	730	97	2.41	996	100	2.58	1350	106	2.72

ABS Whirljet Right Angle Hollow Cone Spray Nozzles have the following features:

- ABS Whirljet Right Angle Hollow Cone Spray Nozzles spray pattern with hollow circle
- Water enter in and vortically spray out through eddy flow passage which makes nozzles not easy for clogging
- Nozzle head is detachable
- Spray angles: 98° to 106°
- Connections: 1/2" (Female)
- General Application :  
Cooling  
Dust suppression  
Chemical treatment  
Washing or cleaning