

Pigtail PP PTFE Plastic Spiral Spray Nozzles



SPJT

Performance Data

Thread size NPT or BSPT	Spray angle (at 0.7 bar)					Flow code	Spray hole Dia.(mm)	Free flowing Dia.(mm)	Flow rate(L/min)				
	60°	90°	120°	150°	170°				0.7bar	1.5bar	3bar	7bar	25bar
1/4	●	●	●			07	2.4	2.4	2.6	3.9	5.5	8.4	16
	●	●	●	●	●	13	3.2	3.2	4.9	7.3	10.3	15.7	30
	●	●	●	●	●	20	4.0	3.2	7.6	11.2	15.8	24	46
3/8	●					07	2.4	2.4	2.6	3.9	5.5	8.4	16
	●					13	3.2	3.2	4.9	7.3	10.3	15.7	30
	●		●	●	●	20	4.0	3.2	7.6	11.2	15.8	24	46
	●	●	●	●	●	30	4.8	3.2	11.4	16.7	24	36	68
	●	●	●	●	●	40	5.6	3.2	15.1	22	32	48	91
	●	●	●	●	●	53	6.4	3.2	20	30	42	64	121
1/2	●	●	●	●	●	82	7.9	3.2	31	46	65	99	187
	●	●	●	●	●	120	9.5	4.8	45	67	95	145	270
3/4	●	●	●	●	●	164	11.1	4.8	62	92	129	198	370
	●	●	●	●	●	210	12.7	4.8	80	117	166	255	480
1	●	●	●	●	●	340	15.9	6.4	130	190	270	410	775
	●	●	●	●	●	470	19.1	6.4	179	260	370	565	1070
1-1/2	●	●	●	●	●	640	22.2	7.9	245	355	505	770	1460
	●	●	●	●	●	820	25.4	7.9	310	455	645	990	1870
	●	●	●	●	●	960	28.6	7.9	365	535	755	1160	2190
2	●	●	●	●	●	1400	34.9	11.1	535	780	1105	1690	3190
	●	●	●	●	●	1780	38.1	11.1	680	995	1405	2150	4060
3	●	●	●			2560	44.5	14.3	980	1430	2020	3090	5830
	●	●	●			3360	50.8	14.3	1280	1880	2650	4050	7660
4	●	●	●			5250	63.5	15.9	2000	2930	4140	6330	11960

Pigtail PP PTFE Plastic Spiral Spray Nozzles have the following features:

- Pigtail PP PTFE Plastic Spiral Spray Nozzles have limited plastic mould NO. They can also be produced in any item No. by machining process.
- Plastic material can be applied to corrosion environments.
- These are one-piece nozzles with no internal vane and a wider free passage
- Spray angles: 120° for mould. Other spray angles can be manufactured by machining method
- Connections: 1/4" to 3" (male NPT and BSPT)
- Operating pressure range: up to 400 psi (25 bar)
- Their special design makes them virtually clog-free and produces a wider spray coverage than other nozzles for a given flow and pressure.
- General Application :
Scrubbing tower or washing tower
Gas cooling
Dust suppression
Fire fighting or fire control